

## Specifications

ITEMS		<b>F18918W</b>
Image Sensor	Image Sensor	1/5" High Definition Color CMOS Sensor
	Display Resolution	640 x 480 Pixels(300k Pixels)
	Lens	Standard:2.8mm, F:2.4 (IR Lens)
	Mini. Illumination	0.5Lux
Lens	Lens Type	Glass Lens
	Visual Angle	67°
Video	Image Compression	MJPEG
	Image Frame Rate	15fps(VGA),30fps(QVGA)
	Resolution	640 x 480(VGA), 320 x 240(QVGA)
	Flip Mirror Images	Vertical / Horizontal
	Light Frequency	50Hz, 60Hz or Outdoor
	Video Parameters	Brightness, Contrast
	Night Visibility	11 IR LEDs, Night visibility up to 8 meters
Audio	Audio Compression	ADPCM
	Input	Built-in Microphone
	Output	Built-in Speaker
PC Requirements	CPU	2.0GHZ or above (suggested 3.0GHZ)
	Memory Size	256MB or above (suggested 1.0GHZ)
	Display Card	64M or above
	Supported OS	Microsoft Windows 2000/XP,Vista,Windows7,Mac OS,Linux
	Browser	IE6/IE7/IE8,Firefox,Safari,Goolge Chrome,other standard browsers
Smart phone Support	Support phone	iphone,Blackberry,Android,Symbian,Windows Mobile,smart phone support JAVA,
Power	Power Supply	DC 5V/2.0A (EU,US,AU,UK plug)
	Power Consumption	7 Watts (Max.)
Network	Ethernet	One 10/100Mbps RJ-45
	Supported Protocol	HTTP,FTP,TCP/IP,UDP,SMTP,DHCP,PPPoE,DDNS,UPnP,GPRS
Wireless	Wireless Standard	IEEE 802.11b/g
	Data Rate	802.11b:11Mbps(Max.) 802.11g:54Mbps(Max.)
	Wireless Security	WEP & WPA & WPA2 Encryption
Physical	Dimension	110(L) x100(W) x108mm(H)
	Gross Weight	768g (Color Box Size:200X120X175mm)
	Net Weight	418g (accessories included)
Environment	Operate Temper.	0° ~ 55°C (14°F ~ 122°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temper.	-10°C ~ 60° (14°F ~ 140°F)
	Storage Humidity	0% ~ 90% non-condensing
Certification	CE,FCC	
Warranty	Limited 1-year warranty	